




SUPPLEMENTARY MANUAL

[QSX-P4B]

REMOVE THE
PASSANGER AND MAIN SEAT.



REMOVE THE SIDE COVERS
FROM FUEL TANK.



REMOVE THE
FRAME COVERS.



Suzuki GSX-S1000

2015-2017



REMOVE THE COVER
FROM FRONT OF THE FUEL TANK.



REMOVE THE
IGNITION SWITCH COVER.



REMOVE THE FUEL TANK.



Suzuki GSX-S1000

2015-2017




REMOVE THE AIRBOX.



**PLUG QSX CONNECTORS IN-LINE
WITH THE IGNITION COIL
CONNECTORS.**
(BLACK, 2-POLE CONNECTORS BELOW AIRBOX)



**MOUNT THE QSX MODULE TO THE
INNER SIDE OF THE FRAME BY THE
SUPPLIED VELCRO STRIPS,
AND SECURE THE CABLES WITH
CABLE TIES.**
(AVOID DIRECT CONTACT WITH HEAT SOURCES,
LIKE THE CYLINDER HEAD.)



Suzuki GSX-S1000

2015-2017



**CONNECT QSX BLACK WIRE
TERMINAL TO CHASSIS GROUND.**



MOUNT THE QSE SENSOR.

(REPLACE THE BOLT WITH THE ONE SUPPLIED.
PLACE THE CONICAL WASHERS AT THE TWO SIDES OF
THE SENSOR LIKE THIS: (O).
TIGHTEN THE BOLT IN
THIS POSITION BY ABOUT 5-6 NM.
IF YOU DO NOT HAVE
A TORQUE WRENCH, TIGHTEN THE BOLT UNTIL THE
SHIFT ARM IS TIGHT ON THE GEARBOX SHAFT.)

(FOR DIFFERENT MOUNTING OPTIONS,
REFER TO THE SENSOR INSTALL GUIDE.)



**TYPICAL POSITION FOR THE
QUICKSHIFTER EASY.**

